



Water Environment Research Foundation
Collaboration. Innovation. Results.

Wastewater Treatment and Reuse

A collage of four images related to wastewater treatment: a close-up of water flowing over a series of orange-brown filter screens; a person in a white lab coat looking through a microscope; a hand holding a glass slide with a circular sample; and a microscopic view of a textured, porous surface.

**FINAL
REPORT**

Develop and Demonstrate Fundamental Basis for Selectors to Improve Activated Sludge Settleability

Co-published by



01-CTS-4

DEVELOP AND DEMONSTRATE FUNDAMENTAL BASIS FOR SELECTORS TO IMPROVE ACTIVATED SLUDGE SETTLABILITY

by:

Donald M.D. Gray (Gabb), Ph.D., P.E., BCEE
Vincent P. De Lange, P.E.
Mark H. Chien

East Bay Municipal Utility District

2006



The Water Environment Research Foundation, a not-for-profit organization, funds and manages water quality research for its subscribers through a diverse public-private partnership between municipal utilities, corporations, academia, industry, and the federal government. WERF subscribers include municipal and regional water and wastewater utilities, industrial corporations, environmental engineering firms, and others that share a commitment to cost-effective water quality solutions. WERF is dedicated to advancing science and technology addressing water quality issues as they impact water resources, the atmosphere, the lands, and quality of life.

For more information, contact:

Water Environment Research Foundation
635 Slaters Lane, Suite 300
Alexandria, VA 22314-1177
Tel: (703) 684-2470 Fax: (703) 299-0742
www.werf.org werf@werf.org

This report was co-published by the following organization. For nonsubscriber sales information, contact:

IWA Publishing
Alliance House, 12 Caxton Street
London SW1H 0QS, United Kingdom
Tel: +44 (0) 20 7654 5500
Fax: +44 (0) 20 7654 5555
www.iwapublishing.com
publications@iwap.co.uk

© Copyright 2006 by the Water Environment Research Foundation. All rights reserved. Permission to copy must be obtained from the Water Environment Research Foundation.

Library of Congress Catalog Card Number: 2005925038

Printed in the United States of America

IWAP ISBN: 1-84339-752-8

This report was prepared by the organization(s) named below as an account of work sponsored by the Water Environment Research Foundation (WERF). Neither WERF, members of WERF, the organization(s) named below, nor any person acting on their behalf: (a) makes any warranty, express or implied, with respect to the use of any information, apparatus, method, or process disclosed in this report or that such use may not infringe on privately owned rights; or (b) assumes any liabilities with respect to the use of, or for damages resulting from the use of, any information, apparatus, method, or process disclosed in this report.

East Bay Municipal Utility District, Oakland, CA

The research on which this report is based was developed, in part, by the United States Environmental Protection Agency (EPA) through Cooperative Agreement No. CR-827345-01 with the Water Environment Research Foundation (WERF). However, the views expressed in this document are solely those of East Bay Municipal Utility District and neither EPA nor WERF endorses any products or commercial services mentioned in this publication. This report is a publication of WERF, not EPA. Funds awarded under the Cooperative Agreement cited above were not used for editorial services, reproduction, printing, or distribution.

This document was reviewed by a panel of independent experts selected by WERF. Mention of trade names or commercial products does not constitute WERF nor EPA endorsement or recommendations for use. Similarly, omission of products or trade names indicates nothing concerning WERF's or EPA's positions regarding product effectiveness or applicability.

ACKNOWLEDGMENTS

The authors would like to express their appreciation to the Project Subcommittee who provided valuable guidance and input throughout the course of this study. They also thank Orange County Sanitation District, Veolia Water, Inc. (formerly USFilter/Vivendi), OMI, Inc., and numerous municipalities across the United States that contributed valuable information to the project database. The authors acknowledge the efforts of the East Bay Municipal Utility District staff who assisted with the selector demonstration project, including David Freitas, Kurt Haunschild, Edward McCormick, John Cloak, Jack Lim, Sue Berg, Clyde Pham, Lisa Servande, Amar Sidhu, Steve Savage, Steve Kallal, and Alexander Borys, as well as a number of Environmental Careers Organization interns, including Andrew Gentile, Chanice Harris, Xiaozhou You, Matt Hoeft, Carl Anderson, and Janet Chuang. The authors would also like to thank Dr. David Jenkins for providing invaluable comments during technical review of the draft and final project reports.

Report Preparation

Principal Investigator:

Donald M.D. Gray (Gabb), Ph.D., P.E., BCEE
East Bay Municipal Utility District

Project Team:

Vincent P. De Lange, P.E.
Mark H. Chien
David R. Williams, P.E.
East Bay Municipal Utility District

H. David Stensel, Ph.D., P.E., BCEE
Gang Xin
University of Washington, Seattle

Elliott Wheeler
OMI, Inc.

Somnath Basu
Veolia Water, Inc.

Mark Esquer, P.E.
Michelle Hetherington, P.E.
Orange County Sanitation District

B. Narayanan, Ph.D., P.E.
Carollo Engineers, Inc.

Bob Kemmerle, P.E.
E2 Consulting Engineers, Inc.

Project Subcommittee

Orris E. Albertson, P.E., BCEE
Enviro Enterprises, Inc.

Glen T. Daigger, Ph.D., P.E., BCEE, NAE
CH2M Hill

M. Truett Garrett, Jr., Sc.D., P.E.
Post, Buckley, Schuh, & Jerrigan

Tung Nguyen
Sydney Water Corp.

Water Environment Research Foundation Staff

Director of Research:	Daniel M. Woltering, Ph.D.
Senior Program Director:	Amit Pramanik, Ph.D.

ABSTRACT AND BENEFITS

Abstract:

Although selectors have been widely applied to control filamentous bulking in activated sludge systems, significant variation exists in design and operating practices and the degree of sludge settleability achieved. The goal of this research was to investigate fundamental issues regarding the growth and control of specific filamentous organisms at bench scale, develop an extensive database of selector design and operating data from full-scale facilities, and demonstrate implementation of full-scale, pilot anaerobic selectors at two large wastewater treatment plants. Based on data collected from 44 facilities, this project examines the relationship between various process parameters and settleability control.

This study identifies the most significant process variables affecting settleability control in three distinct plant categories—short-MCRT with anoxic or anaerobic selectors, short-MCRT with aerobic selectors, and long-MCRT—and provides recommended design and operating ranges based on single-variable regression analysis of a large database of full-scale plant data. The project team has incorporated this information into a computerized selector diagnostic tool that may be used to retrieve recommended design and operating ranges from the current study and the literature based on user input.

Benefits:

- ◆ Evaluates the role of readily assimilable chemical oxygen demand (raCOD) in the growth and control of *Thiothrix* spp.
- ◆ Documents selector performance and operating data from 44 full-scale facilities.
- ◆ Evaluates the relationship between various process variables and settleability control.
- ◆ Demonstrates implementation of full-scale, pilot anaerobic selectors at two facilities.
- ◆ Provides a semi-empirical formula for calculating the “effective” number of selector compartments (N) in a selector zone based on flow conditions and basin geometry when dye study results are not available.
- ◆ Ranks selector design and operating parameters based on the influence on settleability for three different plant categories—short-MCRT with anoxic or anaerobic selectors, short-MCRT with aerobic selectors, and long-MCRT.
- ◆ Provides recommended design and operating ranges for the most critical process variables in each of the three plant categories.
- ◆ Provides a computerized selector diagnostic tool (available on CD-ROM attached to inside of back cover of report) to assist in troubleshooting existing selectors or designing new selectors based on user input and design/operating parameter recommendations from this study and the literature.

Keywords: Selector, filamentous bulking, settleability

TABLE OF CONTENTS

Acknowledgments	iii
Abstract and Benefits	v
List of Tables	ix
List of Figures	x
List of Acronyms	xiv
Executive Summary	ES-1
1.0 Introduction	1-1
1.1 Project Background	1-1
1.2 Project Objectives	1-4
1.3 Project Scope and Approach	1-5
2.0 Literature Review Summary	2-1
2.1 Background	2-1
2.2 Selector Application	2-1
2.3 Filament Type and Occurrence	2-1
2.3.1 Wastewater Characteristics	2-2
2.3.2 Activated Sludge Process Designs	2-3
2.3.3 Operational Conditions	2-4
2.4 Most Common Filaments at Wastewater Treatment Plants	2-5
2.5 Readily Assimilable Substrate Removal Mechanisms	2-6
2.5.1 Substrate Kinetic Selection Based on Growth Kinetics	2-6
2.5.2 Substrate Storage Mechanisms and Kinetic Selection	2-6
2.5.3 Metabolic Selection	2-7
2.5.4 Diffusion-Based Selection	2-7
2.6 Slowly Assimilable Substrate	2-7
2.7 Selector Processes and Designs	2-8
2.7.1 Substrate Removal	2-8
2.7.2 Selector Staging and Configuration	2-8
2.7.3 Selector Design Loadings	2-9
2.8 Full-Scale Selector Operation and Performance	2-10
2.8.1 Aerobic Selectors	2-10
2.8.2 Anoxic Selectors	2-13
2.8.3 Anaerobic Selectors	2-17
2.9 Control of Important Filamentous Organisms	2-17
2.9.1 Control of <i>Microthrix parvicella</i>	2-17
2.9.2 Control of <i>Thiothrix</i>	2-20
2.9.3 Control of Type 021N	2-20
2.10 Summary and Conclusions	2-20
3.0 Laboratory Investigation Summary	3-1
3.1 Introduction	3-1
3.2 Materials and Methods	3-1
3.3 Results and Discussion	3-2
3.3.1 Diluted Sludge Volume Index	3-2

3.3.2	Microscopic Analysis.....	3-3
3.3.3	Batch Testing	3-4
3.3.4	sCOD Uptake Through the Selectors.....	3-6
3.4	Conclusions.....	3-7
4.0	Detailed Plant Investigations	4-1
4.1	Introduction.....	4-1
4.2	Initial Screening Survey.....	4-1
4.3	Data Collection, Processing, and Verification.....	4-1
4.3.1	Data Collection	4-1
4.3.2	Data Processing.....	4-3
4.3.3	Data Verification.....	4-11
4.4	Results and Discussion	4-11
4.4.1	Facility Size and Selector Type Distribution.....	4-11
4.4.2	Plant Flow vs. Settleability	4-12
4.4.3	Selector ICZ F/M vs. Settleability	4-18
4.4.4	Total Selector F/M vs. Settleability	4-19
4.4.5	Selector MCRT vs. Settleability	4-19
4.4.6	Reactor MCRT vs. Settleability.....	4-20
4.4.7	Contact Loading vs. Settleability.....	4-20
4.4.8	Total Selector HRT vs. Settleability	4-21
4.4.9	Ratio of Selector ICZ to Total Selector Volume vs. Settleability.....	4-21
4.4.10	Number of Selector Stages vs. Settleability.....	4-22
4.4.11	MLSS vs. Settleability	4-23
4.4.12	Regression Analysis.....	4-24
4.4.13	Percentile Distribution Analysis	4-71
4.4.14	Computerized Selector Diagnostic Tool.....	4-71
4.5	Conclusions.....	4-71
5.0	Full-Scale Demonstration Projects.....	5-1
5.1	Introduction.....	5-1
5.2	East Bay Municipal Utility District Main Wastewater Treatment Plant	5-1
5.2.1	Background.....	5-1
5.2.2	System Description	5-2
5.2.3	Bench-Scale Anaerobic Selector Evaluation	5-2
5.2.4	Full-Scale Selector Process Modifications	5-4
5.2.5	Selector Design Criteria.....	5-4
5.2.6	Results and Discussion	5-4
5.2.7	Conclusions.....	5-8
5.3	Orange County Sanitation District Plant No. 1.....	5-9
5.3.1	Background.....	5-9
5.3.2	System Description	5-9
5.3.3	Selector Process Modifications.....	5-9
5.3.4	Selector Design Criteria.....	5-9
5.3.5	Results and Discussion	5-10
5.3.6	Conclusions.....	5-13
5.4	Recommendations for Conducting Selector Pilot Studies	5-14

5.5	Comparison of EBMUD and OCSD Anaerobic Selector Performance.....	5-15
5.5.1	Conclusions.....	5-18
6.0	Summary and Conclusions.....	6-1
6.1	Summary	6-1
6.1.1	Long-MCRT Selector Plants.....	6-1
6.1.2	Short-MCRT Anoxic or Anaerobic Selector Plants.....	6-2
6.1.3	Short-MCRT Aerobic Selector Plants	6-3
6.2	Conclusions.....	6-4
Appendix A: Initial Screening and Detailed Plant Investigation Survey Forms		A-1
Appendix B: Summary of Operating Conditions Identified with Common Filamentous Organisms		B-1
Appendix C: Description of Process Data Calculations for Regression Analysis Data Sets.....		C-1
Appendix D: Further Discussion of the Regression Analyses.....		D-1
Appendix E: Percentile Distribution Analysis of Regression Analysis Data Sets.....		E-1
Appendix F: Instructions for Selector Diagnostic Tool.....		F-1
References.....		R-1

LIST OF TABLES

2-1	Summary of Occurrence Conditions of Commonly Observed Filamentous Organisms	2-2
2-2	Combinations of F/M and Aeration Basin DO Level Above Which Low DO Bulking Does Not Occur in Completely Mixed, Continuously Fed Aeration Basins	2-4
2-3	Most Common Filamentous Organisms Reported at Wastewater Treatment Facilities..	2-5
2-4	Recommended Design F/M Loadings for Staged Selectors	2-9
2-5	Summary of Full-Scale Aerobic Selector Operating and Performance Conditions	2-11
2-6	Summary of Full-Scale Anoxic Selector Operating and Performance Conditions.....	2-14
2-7	Summary of Full-Scale Anaerobic Selector Operating and Performance Conditions...	2-18
3-1	Summary of Bench-Scale Reactor Operating Conditions	3-1
3-2	Soluble COD Concentration (mg sCOD/L) Measured Across Three-Stage Selector Reactor (R1).....	3-7
3-3	COD Concentration (mg sCOD/L) Measured Across Four-Stage Selector Reactor (R4)	3-7
4-1	Summary of Detailed Plant Investigation Data Requested.....	4-2
4-2	Summary of Detailed Plant Investigation Process Data Calculations	4-3
4-3	Example Calculation for Estimating BOD ₅ Value Using Linearly Weighted Moving Average	4-9
4-4	Summary of Interpolated Data for Specific Process Variables	4-11
4-5	Summary of Detailed Plant Investigation Data	4-13
4-6	Regression Analysis Trial (A) of Selector Parameters vs. Log DSVI: Long-MCRT WWTPs.....	4-24
4-7	Regression Analysis Trial (B) of Selector Parameters vs. Log DSVI: Long-MCRT WWTPs.....	4-25
4-8	Regression Analysis Trial (C) of Selector Parameters vs. Log DSVI: Long-MCRT WWTPs.....	4-25
4-9	Short-MCRT Plants with Anoxic or Anaerobic Selectors.....	4-27
4-10	Short-MCRT Plants with Aerobic Selectors.....	4-28
4-11	Long-MCRT Plants with Selectors.....	4-29
4-12	Short-MCRT Plants with Anoxic or Anaerobic Selectors: Significant Parameters	4-31
4-13	Short-MCRT Plants with Aerobic Selectors: Significant Parameters	4-32
4-14	Long-MCRT Plants with Selectors: Significant Parameters	4-33
4-15	Recommended Parameter Ranges for Short-MCRT Plants with Anoxic or Anaerobic Selectors	4-51
4-16	Recommended Parameter Ranges for Short-MCRT Plants with Aerobic Selectors	4-61
4-17	Recommended Parameter Ranges for Long-MCRT Plants with Selectors	4-70
5-1	EBMUD Bench-Scale Anaerobic Selector Evaluation Results (MCRT=3.0d).....	5-3
5-2	Summary of Initial EBMUD MWWTP Anaerobic Selector Design and Operating Criteria	5-4
5-3	EBMUD MWWTP Anaerobic Selector Performance and Operating Data.....	5-5
5-4	Summary of Initial OCSD Plant No. 1 Anaerobic Selector Design and Operating Criteria	5-10
5-5	OCSD Plant No. 1 Anaerobic Selector Performance and Operating Data	5-10
5-6	Comparison of EBMUD and OCSD Selector Operating and Performance Data.....	5-16

LIST OF FIGURES

3-1	Diluted Sludge Volume Index in Four Bench-Scale Reactor Systems.....	3-3
3-2	Oxygen Uptake Rate (OUR) Profiles and Soluble COD Concentration during OUR Tests with 850 mg/L Sodium Acetate Addition to R2.....	3-4
3-3	Oxygen Uptake Rate (OUR) Profiles and Soluble COD Concentration during OUR Tests with 850 mg/L Sodium Acetate Addition to Four Bench-Scale Reactor Systems	3-5
3-4	Oxygen Uptake Rate (OUR) Profiles and Soluble COD Concentration during OUR Tests with 220 mg/L Tween 80 Addition (440 mg/L for R3) to Four Bench-Scale Reactor Systems.....	3-6
4-1	Initial Screening Survey Results – Selector Type and Effectiveness	4-2
4-2	Average and 90 th Percentile SVI and DSVI Comparison	4-4
4-3	Measured and Calculated Activated Sludge Influent BOD ₅ Values for OMI Plant No. 4.....	4-10
4-4	Measured and Calculated Wastewater Temperature Values for Veolia Plant No. 1	4-10
4-5	Facility Size, Selector Type Distribution.....	4-11
4-6	Plant Flow vs. 90 th Percentile SVI and DSVI.....	4-12
4-7	Selector ICZ F/M vs. 90 th Percentile SVI and DSVI.....	4-18
4-8	Effective Selector ICZ F/M vs. 90 th Percentile SVI and DSVI	4-18
4-9	Total Selector F/M vs. 90 th Percentile SVI and DSVI.....	4-19
4-10	Selector MCRT vs. 90 th Percentile SVI and DSVI.....	4-19
4-11	Reactor MCRT (excluding clarifier solids) vs. 90 th Percentile SVI and DSVI	4-20
4-12	Contact Loading vs. 90 th Percentile SVI and DSVI.....	4-21
4-13	Total Selector HRT vs. 90 th Percentile SVI and DSVI.....	4-21
4-14	Ratio of Selector ICZ Volume to Total Selector Volume vs. 90 th Percentile SVI and DSVI	4-22
4-15	Number of Selector Stages vs. 90 th Percentile SVI and DSVI	4-22
4-16	Number of Effective Selector Stages vs. 90 th Percentile SVI and DSVI.....	4-23
4-17	MLSS vs. 90 th Percentile SVI and DSVI.....	4-23
4-18a	MLSS vs. Log DSVI - Regression Plot – Short-MCRT Plants with Anoxic or Anaerobic Selectors	4-35
4-18b	MLSS vs. DSVI - Cubic Polynomial Regression Curve – Short-MCRT Plants with Anoxic or Anaerobic Selectors	4-35
4-19a	7-d Average Reactor MCRT vs. Log DSVI - Regression Plot – Short-MCRT Plants with Anoxic or Anaerobic Selectors.....	4-36
4-19b	7-d Average Reactor MCRT vs. DSVI - Cubic Polynomial Regression Curve – Short-MCRT Plants with Anoxic or Anaerobic Selectors.....	4-36
4-20a	Selector F/M vs. Log DSVI - Regression Plot – Short-MCRT Plants with Anoxic or Anaerobic Selectors.....	4-37
4-20b	Selector F/M vs. DSVI - Cubic Polynomial Regression Curve – Short-MCRT Plants with Anoxic or Anaerobic Selectors.....	4-37
4-21a	7-d Average Selector MCRT vs. Log DSVI - Regression Plot – Short-MCRT Plants with Anoxic or Anaerobic Selectors.....	4-38
4-21b	7-d Selector MCRT vs. DSVI - Cubic Polynomial Regression Curve – Short-MCRT Plants with Anoxic or Anaerobic Selectors.....	4-38

4-22a	Number of Selector Stages vs. Log DSVI - Linear Regression Plot – Short-MCRT Plants with Anoxic or Anaerobic Selectors.....	4-39
4-22b	Number of Selector Stages vs. Log DSVI - Cubic Polynomial Regression Plot – Short-MCRT Plants with Anoxic or Anaerobic Selectors.....	4-39
4-22c	Number of Selector Stages vs. DSVI - Cubic Polynomial Regression Curve – Short-MCRT Plants with Anoxic or Anaerobic Selectors.....	4-40
4-22d	Number of Selector Stages (one plant removed) vs. Log DSVI - Linear Regression Plot – Short-MCRT Plants with Anoxic or Anaerobic Selectors.....	4-40
4-22e	Number of Effective Selector Stages vs. Log DSVI - Cubic Polynomial Regression Plot – Short-MCRT Plants with Anoxic or Anaerobic Selectors.....	4-41
4-22f	Number of Effective Selector Stages vs. DSVI - Cubic Polynomial Regression Curve – Short-MCRT Plants with Anoxic or Anaerobic Selectors.....	4-41
4-22g	Number of Effective Selector Stages (one plant removed) vs. Log DSVI - Cubic Polynomial Regression Plot – Short-MCRT Plants with Anoxic or Anaerobic Selectors.....	4-42
4-22h	Number of Effective Selector Stages (one plant removed) vs. DSVI – Cubic Polynomial Regression Curve – Short-MCRT Plants with Anoxic or Anaerobic Selectors.....	4-42
4-23a	Aeration Basin DO vs. Log DSVI - Cubic Polynomial Regression Plot – Short-MCRT Plants with Anoxic or Anaerobic Selectors.....	4-43
4-23b	Aeration Basin DO vs. DSVI - Cubic Polynomial Regression Curve – Short-MCRT Plants with Anoxic or Anaerobic Selectors.....	4-43
4-24a	Activated Sludge Influent BOD ₅ /TSS Ratio vs. Log DSVI - Cubic Polynomial Regression Plot – Short-MCRT Plants with Anoxic or Anaerobic Selectors.....	4-44
4-24b	Activated Sludge Influent BOD ₅ /TSS Ratio vs. DSVI - Cubic Polynomial Regression Curve – Short-MCRT Plants with Anoxic or Anaerobic Selectors.....	4-44
4-25a	ICZ F/M vs. Log DSVI – Cubic Polynomial Regression Plot – Short-MCRT Plants with Anoxic or Anaerobic Selectors.....	4-45
4-25b	ICZ F/M vs. DSVI – Cubic Polynomial Regression Curve – Short-MCRT Plants with Anoxic or Anaerobic Selectors.....	4-45
4-26a	Nominal Selector HRT (without recycle) vs. Log DSVI – Cubic Polynomial Regression Plot – Short-MCRT Plants with Anoxic or Anaerobic Selectors.....	4-46
4-26b	Nominal Selector HRT (without recycle) vs. DSVI – Cubic Polynomial Regression Curve – Short-MCRT Plants with Anoxic or Anaerobic Selectors.....	4-46
4-27a	Selector Volume to Total Basin Volume Ratio vs. Log DSVI – Cubic Polynomial Regression Plot – Short-MCRT Plants with Anoxic or Anaerobic Selectors.....	4-47
4-27b	Selector Volume to Total Basin Volume Ratio vs. DSVI – Cubic Polynomial Regression Curve – Short-MCRT Plants with Anoxic or Anaerobic Selectors.....	4-47
4-28a	ICZ HRT (with RAS) vs. Log DSVI – Cubic Polynomial Regression Plot – Short-MCRT Plants with Anoxic or Anaerobic Selectors.....	4-48
4-28b	ICZ HRT (with RAS) vs. DSVI – Cubic Polynomial Regression Curve – Short-MCRT Plants with Anoxic or Anaerobic Selectors.....	4-48
4-28c	Effective ICZ HRT (with RAS) vs. Log DSVI – Cubic Polynomial Regression Plot – Short-MCRT Plants with Anoxic or Anaerobic Selectors.....	4-49
4-28d	Effective ICZ HRT (with RAS) vs. DSVI – Cubic Polynomial Regression Curve – Short-MCRT Plants with Anoxic or Anaerobic Selectors.....	4-49

4-29a	Effluent Temperature vs. Log DSVI – Cubic Polynomial Regression Plot – Short-MCRT Plants with Anoxic or Anaerobic Selectors.....	4-50
4-29b	Effluent Temperature vs. DSVI – Cubic Polynomial Regression Curve – Short-MCRT Plants with Anoxic or Anaerobic Selectors.....	4-50
4-30a	Activated Sludge Influent BOD vs. Log DSVI – Cubic Polynomial Regression Plot – Short-MCRT Plants with Aerobic Selectors.....	4-52
4-30b	Activated Sludge Influent BOD vs. DSVI – Cubic Polynomial Regression Curve – Short-MCRT Plants with Aerobic Selectors	4-52
4-31a	Nominal ICZ HRT (without recycle) vs. Log DSVI – Cubic Polynomial Regression Plot – Short-MCRT Plants with Aerobic Selectors	4-53
4-31b	Nominal ICZ HRT (without recycle) vs. DSVI – Cubic Polynomial Regression Curve – Short-MCRT Plants with Aerobic Selectors.....	4-53
4-32a	ICZ HRT (with recycle) vs. Log DSVI – Cubic Polynomial Regression Plot – Short-MCRT Plants with Aerobic Selectors	4-54
4-32b	ICZ HRT (with recycle) vs. DSVI – Cubic Polynomial Regression Curve – Short-MCRT Plants with Aerobic Selectors.....	4-54
4-33a	Effluent pH vs. Log DSVI – Cubic Polynomial Regression Plot – Short-MCRT Plants with Aerobic Selectors.....	4-55
4-33b	Effluent pH vs. DSVI – Cubic Polynomial Regression Curve – Short-MCRT Plants with Aerobic Selectors	4-55
4-34a	Nominal Selector HRT (without recycle) vs. Log DSVI – Cubic Polynomial Regression Plot – Short-MCRT Plants with Aerobic Selectors.....	4-56
4-34b	Nominal Selector HRT (without recycle) vs. DSVI – Cubic Polynomial Regression Curve – Short-MCRT Plants with Aerobic Selectors	4-56
4-35a	Percent RAS Flow vs. Log DSVI – Cubic Polynomial Regression Plot – Short-MCRT Plants with Aerobic Selectors.....	4-57
4-35b	Percent RAS Flow vs. DSVI – Cubic Polynomial Regression Curve – Short-MCRT Plants with Aerobic Selectors.....	4-57
4-36a	Effluent Temperature vs. Log DSVI – Cubic Polynomial Regression Plot – Short-MCRT Plants with Aerobic Selectors.....	4-58
4-36b	Effluent Temperature vs. DSVI – Cubic Polynomial Regression Curve – Short-MCRT Plants with Aerobic Selectors.....	4-58
4-37a	ICZ F/M vs. Log DSVI – Cubic Polynomial Regression Plot – Short-MCRT Plants with Aerobic Selectors	4-59
4-37b	ICZ F/M vs. DSVI – Cubic Polynomial Regression Curve – Short-MCRT Plants with Aerobic Selectors	4-59
4-38a	MLSS vs. Log DSVI – Cubic Polynomial Regression Plot – Short-MCRT Plants with Aerobic Selectors	4-60
4-38b	MLSS vs. DSVI – Cubic Polynomial Regression Curve – Short-MCRT Plants with Aerobic Selectors	4-60
4-39a	MLSS vs. Log DSVI – Cubic Polynomial Regression Plot – Long-MCRT Plants with Selectors	4-62
4-39b	MLSS vs. DSVI – Cubic Polynomial Regression Curve – Long-MCRT Plants with Selectors	4-62
4-40a	Selector HRT (with recycle) vs. Log DSVI – Cubic Polynomial Regression Plot – Long-MCRT Plants with Selectors	4-63

4-40b	Selector HRT (with recycle) vs. DSVI – Cubic Polynomial Regression Curve – Long-MCRT Plants with Selectors	4-63
4-41a	Selector Volume to Total Basin Volume Ratio vs. Log DSVI – Cubic Polynomial Regression Plot – Long-MCRT Plants with Selectors	4-64
4-41b	Selector Volume to Total Basin Volume Ratio vs. DSVI – Cubic Polynomial Regression Curve – Long-MCRT Plants with Selectors	4-65
4-42a	Number of Aeration Basin Stages vs. Log DSVI – Cubic Polynomial Regression Plot – Long-MCRT Plants with Selectors	4-65
4-42b	Number of Aeration Basin Stages vs. DSVI – Cubic Polynomial Regression Curve – Long-MCRT Plants with Selectors	4-66
4-43a	Number of Selector Stages vs. Log DSVI – Cubic Polynomial Regression Plot – Long-MCRT Plants with Selectors	4-66
4-43b	Number of Selector Stages vs. DSVI – Cubic Polynomial Regression Curve – Long-MCRT Plants with Selectors	4-67
4-43c	Number of Effective Selector Stages vs. Log DSVI – Cubic Polynomial Regression Plot – Long-MCRT Plants with Selectors	4-67
4-43d	Number of Effective Selector Stages vs. DSVI – Cubic Polynomial Regression Curve – Long-MCRT Plants with Selectors	4-67
4-44a	Effluent pH vs. Log DSVI – Cubic Polynomial Regression Plot – Long-MCRT Plants with Selectors	4-68
4-44b	Effluent pH vs. DSVI – Cubic Polynomial Regression Curve – Long-MCRT Plants with Selectors	4-68
4-45a	Effluent Temperature vs. Log DSVI – Cubic Polynomial Regression Plot – Long-MCRT Plants with Selectors	4-69
4-45b	Effluent Temperature vs. DSVI – Cubic Polynomial Regression Curve – Long-MCRT Plants with Selectors	4-69
5-1	EBMUD SVI Percentile Distribution and Dominant Filament Results.....	5-2
5-2	EBMUD Bench-Scale Selector and Control DSVI (following seeding) at MCRT=3.0d	5-3
5-3	EBMUD MWWTP Full-Scale Selector and Control SVI, Aerated MCRT, MLSS	5-6
5-4	EBMUD MWWTP Full-Scale Selector and Control <i>Nocardia</i> Counts	5-7
5-5	EBMUD MWWTP Full-Scale Selector Ortho-P Release and Uptake, Influent Volatile Fatty Acids (VFAs).....	5-8
5-6	EBMUD MWWTP Full-Scale Control Ortho-P Levels, Influent VFAs	5-8
5-7	OCSD Selector and Control SVI	5-12
5-8	OCSD Selector and Control MCRT	5-12
5-9	OCSD Selector and Control Stage 1 Orthophosphate Concentration.....	5-13
5-10	OCSD Reactor MCRT, SVI, and Stage 1 Orthophosphate Concentration.....	5-13

LIST OF ACRONYMS

BOD	biochemical oxygen demand
BNR	biological nutrient removal
CMAS	completely mixed activated sludge
COD	chemical oxygen demand
CSTR	continuous-flow stirred tank reactor
DNA	deoxyribose nucleic acid
DO	dissolved oxygen
DSVI	diluted sludge volume index
EBMUD	East Bay Municipal Utility District
EBPR	enhanced biological phosphorus removal
F/M	food-to-microorganism ratio
GAO	glycogen-accumulating organism
HP	horsepower
HRT	hydraulic residence time
ICZ	initial contact zone
LCFA	long-chain fatty acid
MCRT	mean cell residence time
MLSS	mixed liquor suspended solids
mV	millivolts
MWWTP	Main Wastewater Treatment Plant (EBMUD)
OCSD	Orange County Sanitation District
OUR	oxygen uptake rate
PAO	phosphorus-accumulating organism
PHB	poly- β -hydroxybutyrate
RAS	return activated sludge
raCOD	readily assimilable COD
rRNA	ribosomal ribose nucleic acid
saCOD	slowly assimilable COD
sCOD	soluble COD
SBR	sequencing batch reactor
SCFA	short-chain fatty acid
SSV ₃₀	30-min settled sludge volume
SVI	sludge volume index
TAG	triglyceride
UCT	University of Cape Town (South Africa)
UOSA	Upper Occoquan Sewage Authority
VIF	variance inflation factor
WAS	waste activated sludge

EXECUTIVE SUMMARY

ES.1 Key Findings

In brief, this study supports the following conclusions:

- ◆ Anoxic selectors do not appear to control filamentous bulking in long-mean cell residence time (MCRT) plants. In fact, the elimination of all anoxic zones may help to control bulking in these plants. Other design/operating parameters, however, were shown to influence activated sludge settleability in long-MCRT plants.
- ◆ Aerobic selectors in short-MCRT plants do control filamentous bulking if they are small enough to produce a biochemical oxygen demand (BOD) concentration gradient in the aeration basins.
- ◆ Anoxic and anaerobic selectors do control filamentous bulking in short-MCRT plants if the selector volume is large enough and/or the selector mixed liquor suspended solids concentration is high enough. These selector systems do not appear to benefit from a BOD concentration gradient as the aerobic selectors in short-MCRT plants do. Although anaerobic/anoxic selector compartmentalization in these plants appears to improve settleability, this is presumably because of reduced selector short-circuiting.

To make the study findings more readily available to practitioners, the project team prepared a computerized selector diagnostic tool, which is included on a CD-ROM attached to the inside back cover of this report. Documentation for this software application is provided in Appendix F, which explains the simple steps to using the selector diagnostic tool software. This study's findings can be used immediately through this software to help an operator troubleshoot a poorly-performing selector or help an engineer design a better-performing selector.

If the practitioner is interested in how the selector diagnostic tool's guidelines were derived, Chapter 4.0 can be referenced. If the practitioner is interested in an actual demonstration of these guidelines, Chapter 5.0 can be referenced. Chapter 6.0 provides a more detailed summary of the study's findings and conclusions, Chapter 2.0 provides a selector literature review, and Chapter 3.0 provides laboratory study results demonstrating the role of readily assimilable chemical oxygen demand (raCOD) in selector performance. Refer to the discussion on raCOD in Chapter 1.0, Page 1-3.

As shown in Chapter 5.0, a selector system does not need to comply with all the design/operating parameter ranges listed in the selector diagnostic tool's results tables to control filamentous bulking. The East Bay Municipal Utility District (EBMUD) selector worked well and only complied with three parameters. Since the parameters are listed in order of their influence on diluted sludge volume index (DSVI), those listed first in the diagnostic tool's results table are those that the selector operator or designer should be primarily concerned with.

A more detailed summary of this study's findings is presented in the next section.

ES.2 Project Objectives

Selector processes have been widely applied to control filamentous bulking in activated sludge systems for more than thirty years. Still, the literature does not provide a consistent set of selector process design or operating guidelines. Variation in the degree of sludge settleability

control achieved, represented by the sludge volume index (SVI), for similar process designs has dictated that selectors be designed on an empirical basis, relying heavily on design concepts and demonstrated performance at facilities with similar wastewater characteristics and process configurations.

The primary objectives of this research were to:

- ◆ Investigate the mechanisms limiting the ability of a selector to control the growth of specific filamentous organisms known to cause bulking;
- ◆ Establish a project database of selector design and performance from a large pool of full-scale facilities from across the U.S.;
- ◆ Identify selector design and performance relationships for each of the three main selector categories (aerobic, anoxic, and anaerobic) based on the project database information collected; and
- ◆ Demonstrate the implementation of a full-scale anaerobic selector at two wastewater treatment facilities and identify associated selector design and performance issues.

ES.3 Project Approach

Based on the project objectives, this study was divided into five main project tasks:

1. Literature Review
2. Laboratory Investigation
3. Initial Plant Screening Survey
4. Detailed Plant Investigations
5. Full-Scale Demonstration Projects

Dr. H. David Stensel (University of Washington, Seattle) conducted a literature search and review of selector-related topics, including filament type and occurrence in activated sludge systems, kinetic and metabolic substrate removal mechanisms, available full-scale selector design and performance data, and current research efforts related to the control of specific filamentous organisms. The goal of the literature review was to highlight key issues for application to subsequent project tasks.

The literature review illustrated that selector design approaches are focused on the removal of raCOD, while some selector designs often fail if process conditions favor the growth of filamentous organisms that thrive on slowly assimilable chemical oxygen demand (saCOD). In order to further examine this issue, under Dr. Stensel's direction, Gang Xin conducted a bench-scale, laboratory experiment to investigate the ability of an aerobic selector to control two specific filamentous organism types—one that prefers raCOD (Type 021N, *Thiothrix*) and one that thrives on saCOD (*Microthrix parvicella*, Type 0092).

This study focused primarily on collecting and analyzing selector design and operating data from full-scale facilities from across the U.S. As an initial step, a screening survey form, designed to be completed in a relatively short time period, was distributed to a large number of wastewater facilities from across the country. The initial screening survey was used to establish plant contacts at a large pool of facilities equipped with selectors of various types, collect basic selector design (type, configuration) and performance data (SVI), and identify candidate facilities interested in participating further in the study.

Following completion of the initial screening survey, many of the facilities were carried forward as part of a detailed plant investigation task. During this phase, plants were asked to

provide more detailed information regarding both plant and selector design and operation, including one year of plant operating and selector performance data. Based on the activated sludge operating data provided, a number of important design parameters were calculated in order to compare selector design and performance between facilities and selector types. For the purposes of this study, the diluted SVI (DSVI) was selected as the most accurate representation of sludge settleability at these facilities because of the dependency of the SVI test on mixed liquor suspended solids (MLSS) concentration. Single variable regression analyses were conducted to evaluate the relationship between a wide array of process variables and the DSVI achieved (dependent variable). The results were compared to literature design and operating guidelines whenever possible.

Since selectors are often installed as retrofits to existing facilities rather than included in original plant designs, this study included the performance demonstration of full-scale anaerobic selectors installed at two wastewater treatment facilities—the EBMUD Main Wastewater Treatment Plant (MWWTP) in Oakland, Calif., and the Orange County Sanitation District (OCSd) Plant No. 1 in Fountain Valley, Calif. The goal of this work was to provide municipalities with key information necessary for successful selector implementation at their facilities by highlighting process considerations and issues.

ES.4 Literature Review

The following is a summary of the main literature review findings:

- ◆ A combined survey of 270 U.S. facilities (Jenkins et al. 2004) indicated that the most common filament types were (in order of frequency of occurrence) Type 1701, Type 021N, and *Thiothrix*, while a survey of 33 long-MCRT, biological nutrient removal (BNR) plants in South Africa (Blackbeard et al., 1987) found Type 0092, Type 0675, Type 0041, *M. parvicella*, and Type 0914 to be most common.
- ◆ Aerobic selectors promote kinetic conditions favoring preferential substrate uptake and sequestering by floc-formers over filamentous organisms. Anoxic selectors create a metabolic advantage for floc-formers, since most filamentous organisms are unable to denitrify (use nitrate as an electron acceptor) or have relatively low denitrification rates. Similarly, the feed-starve cycle employed in anaerobic selectors allows metabolic selection of floc-forming, phosphorus-accumulating organisms (PAOs) or glycogen-accumulating organisms (GAOs) over filamentous organisms.
- ◆ Selectors will be most successful in situations where the target filaments use raCOD as substrates. Selectors may fail if the target filament uses saCOD or sulfide or is favored by low pH or nutrient deficient conditions.
- ◆ Some filament types, such as *M. parvicella*, use saCOD [long-chain fatty acids (LCFAs)] for substrate and will proliferate in selector systems under the following conditions: zero or low dissolved oxygen (DO), long MCRT, and low temperature.
- ◆ A review of pilot- and full-scale selector design and operating data showed that a wide range of SVI control was achieved, with some installations reporting no significant improvement in bulking control. Single-stage designs are used for anoxic and anaerobic selectors, while most aerobic selectors include a staged design.

The following is a summary of general selector design guidelines found in the literature:

- ◆ Substrate Removal – The soluble COD (sCOD) leaving the selector should be <60 mg/L (Shao and Jenkins, 1989) and the raCOD should be virtually absent. The selector should remove 80% of the removable COD (Chudoba and Wanner, 1987).
- ◆ Selector Staging and Configuration – All three selector types (aerobic, anoxic, anaerobic) should be designed with at least three stages, sized at 25%, 25%, and 50% of the total selector volume, respectively (Jenkins et al., 2004). A staged-selector arrangement is necessary to create a food-to-microorganism (F/M) gradient (Albertson, 2005).
- ◆ Aerobic Selectors – Aerobic selectors should be staged to provide proper kinetic conditions favoring rapid substrate uptake and storage by floc-formers over filaments. Jenkins et al. (2004) recommended a three-stage design, sized at 25%, 25%, and 50% of the total selector volume with first stage and total F/M loadings of 12 kg COD/(kg MLSS·d) and 3 kg COD/(kg MLSS·d), respectively.
- ◆ Anoxic Selectors – In single-stage arrangements, the selector F/M should be ≤ 1 kg BOD₅/(kg MLSS·d) for temperatures $\leq 18^{\circ}\text{C}$ and ≤ 1.5 kg BOD₅/(kg MLSS·d) for temperatures $> 18^{\circ}\text{C}$, while the anoxic MCRT should be at 1-2 d (Marten and Daigger, 1997). Grady et al. (1999) recommended an anoxic MCRT of 1.0 d at temperatures $> 20^{\circ}\text{C}$ and 1.5 d at temperatures $< 17^{\circ}\text{C}$. Jenkins et al. (2004) recommended a three-stage design, sized at 25%, 25%, and 50% of the total selector volume with first-stage and total F/M loadings of 6 kg COD/(kg MLSS·d) and 1.5 kg COD/(kg MLSS·d), respectively.
- ◆ Anaerobic Selectors – A three-stage selector with a total selector hydraulic residence time (HRT) of 0.75–2.0 h is recommended (Jenkins et al., 2004).

ES.5 Laboratory Investigation

Four 3-L bench-scale, completely mixed activated sludge (CMAS) units (R1, R2, R3, and R4) were initially seeded with activated sludge containing both *Thiothrix* spp. (raCOD filament) and *M. parvicella* (saCOD filament). The reactors were fed a synthetic wastewater high in Tween 80 (water soluble oleic acid ester of sorbitol) and acetate to promote the growth of both raCOD and saCOD filament types. After an initial startup period, the following changes were made: 1) a three-stage aerobic selector was added to R1 (25%, 25%, and 50% of total selector volume), 2) the raCOD constituents were removed from the feed to R2, and 3) a four-stage aerobic selector was added to R4 (12.5%, 12.5%, 25%, and 50% of total selector volume). No changes were made to R3, which served as the control. Oxygen uptake rate (OUR) batch tests were conducted periodically by adding either acetate (raCOD) or Tween 80 (saCOD) to mixed liquor samples from each reactor. The reactor operating conditions are summarized in Table ES-1.

Table ES-1. Summary of Bench-Scale Reactor Operating Conditions.

Reactor No.	Description	Operating Conditions (all reactors)			
		Wastewater Feed	MCRT(d)	Temp. (°C)	Air Feed
1	Three-stage aerobic selector	Synthetic, high in LCFAs (oleic acid) and raCOD (acetate)	20	12–15	Intermittent, DO between 0–2 mg/L
2	raCOD removal from feed				
3	Single-stage CSTR				
4	Four-stage aerobic selector				

The DSVI variation over time in each of the four bench-scale units is shown in Figure ES-1. The results suggest that adding a three-stage and four-stage aerobic selector to R1 and R4, respectively, had a similar effect on DSVI reduction as removing raCOD from the feed to R2. The systems equipped with selectors, however, actually achieved slightly improved DSVI values, suggesting that aerobic selectors may do more to control bulking than just remove raCOD. Severe bulking occurred in the control reactor with *Thiothrix* spp. as the dominant filament type. Conditions favoring the growth of *M. parvicella* could not be maintained in any of the reactors.




Figure ES-1. Dilute Sludge Volume Index in Four Bench-scale Reactor Systems.

OUR and acetate uptake rates were dramatically reduced in R2 following raCOD removal from the wastewater feed and were significantly less (2-6 times lower for OUR, 3-7 times lower for acetate) than the other reactors. This suggests that the R2 feed without raCOD did not support raCOD floc-forming bacteria growth and that the presence of these bacteria may enhance floc structure and settleability. Acetate uptake rates were 6–10 times higher than the Tween 80 uptake rates, which suggests that Tween 80 (and possibly all LCFAs) may not be adequately removed in a selector and could leak into the main aeration zone at sufficient levels to support filamentous bulking. Similar DSVI control was achieved in both the three- and four-stage aerobic selector systems, while sCOD profiles indicated that most of the removal occurred in the first stage.

ES.6 Initial Plant Screening Survey

The initial screening survey included 125 U.S. wastewater treatment plants. Of these facilities, 85 had selectors (aerobic, anoxic, or anaerobic), but only 46 had improved settleability following selector installation, as shown in Figure ES-2.




Figure ES-2. Initial Screening Survey Results – Selector Type and Effectiveness.

The initial screening survey form requested the following basic plant information:

- ◆ Plant flow rate
- ◆ MCRT
- ◆ Nutrient removal requirements
- ◆ Aeration basin configuration
- ◆ Type of selector
- ◆ Bulking frequency
- ◆ SVI control achieved following selector installation

Given the significant amount of additional plant data to be requested and assuming a moderate response rate, the project team decided to carry forward all 85 facilities reporting selector installations to the detailed plant investigation phase.

ES.7 Detailed Plant Investigations

Table ES-2 summarizes the information requested from each of the 85 facilities included in the detailed plant investigation. In addition to collecting general plant and process configuration information, each facility was asked to provide approximately one year of selector operating and performance data in spreadsheet format. The extensive data collection effort required numerous follow-up data requests and discussions with plant contacts to verify the information provided and to answer plant-specific questions. A number of important selector design and operating parameters were calculated based on the information provided by each plant, as summarized in Table ES-3.

Most facilities reported sludge settleability performance on an SVI basis. Given the dependence of the SVI test result on mixed liquor concentration, as reported by Dick and Vesilind (1969), reported SVI values were converted to DSVIs by applying a correction developed by Merkel (1971). Lee et al. (1983) reported that the DSVI test yielded the best

correlation with total extended filament length relative to other techniques for estimating sludge settleability.

Table ES-2. Summary of Detailed Plant Investigation Data Requested.

Category	Description
General Information	• Facility name, location, contact • Average, peak flow rate • Industrial contribution, major contributors • Annual wastewater temperature range • Nutrient removal requirements and processes
Selector Configuration	• Selector type (aerobic, anoxic, anaerobic) • Number and volume of selector stages • Mixing type (hydraulic, mechanical, air) • Available process design criteria, technical reports
Aeration Basin Configuration	• Number and volume of aeration stages and basins • Type of aeration system • Internal recycle streams • Approximate DO profiles • Location of RAS feed points
Additional Plant Information	• Process schematic • Secondary process operation and maintenance (O&M) manuals • Secondary influent sulfide levels • Oxygen uptake rate data • Soluble BOD or COD exiting the selector zone
Plant Operating Data (One Year)	• Secondary influent – flow, BOD, sBOD, COD, sCOD, TKN, P • Number of aeration basins in-service • WAS, RAS flow and concentration • MLSS, MLVSS • System (excluding clarifier solids), aerated MCRT • F/M • DO • Influent or effluent pH • SVI or DSVI • Filament type and abundance • RAS chlorination periods

Table ES-3. Summary of Detailed Plant Investigation Process Data Calculations.

Parameter	Comments
Selector MCRT (d)	Calculation based on mass of mixed liquor in selector zone only
Contact (or floc) loading (kg BOD ₅ /kg MLSS)	Ratio of influent BOD mass to solids mass in initial contact zone (ICZ)
Selector ICZ F/M loading [kg BOD ₅ /(kg MLSS·d)]	F/M calculation based on mass of mixed liquor in selector ICZ only
Selector HRT (h)	HRT calculation based on volume of selector zone only
90 th Percentile SVI (mL/g)	
90 th Percentile Merkel DSVI (mL/g)	SVI data converted to DSVI using Merkel equation
Fraction of SVIs greater than 150 mL/g (%)	Represents percent of time SVIs exceed typical control limit

Given the large amount of information requested from each facility, many facilities were not able to provide key information, such as filament type and abundance, SVI, or essential secondary process operating data. Despite this limitation, the study was successful in collecting and verifying data from 44 of the 85 original plants for a total of 48 data sets (four facilities included two data sets representing distinct operating modes). The facility size and selector type distribution is presented in Figure ES-3. A tabular summary of all data collected is included in Table 4-5 in the main report.




Figure ES-3. Facility Size, Selector Type Distribution.

Average values for a number of selector process design parameters were plotted against both 90th percentile SVI and DSVI results (including the Merkel correction, as necessary). Figure ES-4 is a plot of the ICZ F/M, selector F/M, selector MCRT, system MCRT (excluding clarifier solids), total selector HRT, and number of selector stages versus 90th percentile DSVI. For the purposes of this study, a 90th percentile DSVI value of 150 mL/g was selected as the typical upper limit for well-settling sludge.

The plots in Figure ES-4 clearly indicate that the anoxic selectors achieved greater bulking control relative to the anaerobic selectors. Nearly all of the anoxic selector facilities (23 of 27) had 90th percentile DSVIs <150 mL/g, while nearly all of the anaerobic selector plants (12 of 14) exceeded this limit. Two of five aerobic selector plants also exceeded 150 mL/g. Most anoxic selectors, however, were installed in long-MCRT plants, while all anaerobic selectors were installed in short-MCRT plants (see Figure ES-4). Therefore, the lower DSVI in plants with anoxic selectors may be because of the lower DSVI produced by long-MCRT filamentous bacteria (Wanner, 1994), rather than selector type.

No clear relationships were observed between settleability control and selector ICZ F/M, selector F/M, selector MCRT, system MCRT (excluding clarifier solids), or total selector HRT. In fact, a wide range of DSVIs was observed across a broad range of F/M loading rates, MCRTs, and selector HRTs. Selector staging was not observed to have a significant impact on bulking control in the anoxic selector systems. All eight single-stage anoxic selectors yielded DSVIs <150 mL/g, while four of 18 multi-stage anoxic selectors exceeded this limit. Selector staging was also not observed to have a significant impact on settleability in anaerobic selector systems, since six of seven plants yielded DSVIs >150 mL/g in both the single- and multi-stage categories.